PROFESSIONAL TORQUE WRENCH RATCHET 'P' TYPE



For production line applications requiring a sealed torque setting. 'P' Type wrenches have no scale and must be set against a suitable torque measuring device (see pages 42 - 45).

- Accurate to within $\pm 3\%$ of torque setting
- Colour coded adjustment seals and locking tool provided
- On request 'P'Type wrenches can be set, marked with the setting and certified for production line applications requiring a sealed torque setting.



• Push through ratchet allows clockwise and anti-clockwise torque control

2	PRODUCTION 'P' TYPE - INDUSTRIAL RATCHET (Push through square)
13051	Pro 60, ¾", 8 - 60 N·m, 5 - 45 lbf·ft
13052	Pro 60, 1⁄2", 8 - 60 N·m, 5 - 45 lbf·ft
13053	Pro 100, ³∕ø ", 20 - 100 N·m, 15 - 80 lbf·ft
13054	Pro 100, 1/2", 20 - 100 N·m, 15 - 80 lbf·ft
13055	Pro 200, ½", 40 - 200 N·m, 30 - 150 lbf·ft
13057	Pro 300, 1⁄2", 60 - 300 N·m, 45 - 220 lbf·ft
13056	Pro 400, 3⁄4" 80 - 400 N·m, 60 - 300 lbf·ft
11698	Domed End Cap
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)



• Reversible, 72 tooth ratchet

2	PRODUCTION 'P' TYPE AUTOMOTIVE RATCHET (Reversible)
11164	Pro 60, ¾, 8 - 60 N·m, 5 - 45 lbf·ft
11171	Pro 60, 1⁄2", 8 - 60 N·m, 5 - 45 lbf·ft
11138	Pro 100, 3/8", 20 - 100 N·m, 15 - 80 lbf·ft
11139	Pro 100, 1/2", 20 - 100 N·m, 15 - 80 lbf·ft
11140	Pro 200, 1⁄2", 40 - 200 N·m, 30 - 150 lbf·ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)

PROFESSIONAL TORQUE HANDLE 'P' TYPE

🐵 🔒 🗩 🕯





Setting a 'P' Type Torque Wrench



2	TORQUE HANDLES PRODUCTION 'P' TYPE 16mm SPIGOT
11167	Pro 60, 16mm spigot, 8 - 60 N·m, 5 - 45 lbf·ft
11143	Pro 100, 16mm spigot, 20 - 100 N·m, 15 - 80 lbf·ft
11144	Pro 200, 16mm spigot, 40 - 200 N·m, 30 - 150 lbf·ft
11117	Pro 300, 16mm spigot, 60 - 300 N·m, 45 - 220 lbf·ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)



2	FEMALE TORQUE HANDLES PRODUCTION 'P' TYPE
11170	Pro 60, 9 x 12mm, 8 - 60 N·m, 5 - 45 lbf·ft
11150	Pro 100, 9 x 12mm, 20 - 100 N·m, 15 - 80 lbf·ft
11151	Pro 200, 9 x 12mm, 40 - 200 N·m, 30 - 150 lbf·ft
11152	Pro 200, 14 × 18mm, 40 - 200 N·m, 30 - 150 lbf·ft
11153	Pro 300, 14 x 18mm, 60 - 300 N·m, 45 - 220 lbf·ft
13068	Pro 400, 14 × 18mm, 80 - 400 N·m, 60 - 300 lbf·ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)

9 19