



2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - DUAL SCALE

15062	Pro 50, 16mm spigot, 10 - 50 N·m, 7.5 - 37.5 lbf·ft
15063	Pro 100, 16mm spigot, 20 - 100 N·m, 15 - 75 lbf·ft
15064	Pro 200, 16mm spigot, 40 - 200 N·m, 30 - 150 lbf·ft
15065	Pro 300, 16mm spigot, 60 - 300 N·m, 50 - 220 lbf·ft

2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - N·m ONLY

15072	Pro 50, 16mm spigot, 10 - 50 N·m
15073	Pro 100, 16mm spigot, 20 - 100 N·m
15074	Pro 200, 16mm spigot, 40 - 200 N·m
15075	Pro 300, 16mm spigot, 60 - 300 N·m

2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - lbf·ft ONLY

15082	Pro 50, 16mm spigot, 7.5 - 37.5 lbf·ft
15083	Pro 100, 16mm spigot, 15 - 75 lbf·ft
15084	Pro 200, 16mm spigot, 30 - 150 lbf·ft
15085	Pro 300, 16mm spigot, 50 - 220 lbf·ft

2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - lbf·in ONLY

15092	Pro 50, 16mm spigot, 90 - 440 lbf·in
15093	Pro 100, 16mm spigot, 200 - 800 lbf·in
15094	Pro 200, 16mm spigot, 400 - 1800 lbf·in
15095	Pro 300, 16mm spigot, 500 - 2500 lbf·in



2 FEMALE TORQUE HANDLES ADJUSTABLE - DUAL SCALE

15102	Pro 50, 9 x 12mm, 10 - 50 N·m, 7.5 - 37.5 lbf·ft
15103	Pro 100, 9 x 12 mm, 20 - 100 N·m, 15 - 75 lbf·ft
15104	Pro 200, 9 x 12 mm, 40 - 200 N·m, 30 - 150 lbf·ft
15105	Pro 200, 14 x 18 mm, 40 - 200 N·m, 30 - 150 lbf·ft
15106	Pro 300, 14 x 18 mm, 60 - 300 N·m, 50 - 220 lbf·ft
15107	Pro 340, 14 x 18 mm, 60 - 340 N·m, 50 - 250 lbf·ft
15108	Pro 400, 14 x 18 mm, 80 - 400 N·m, 60 - 300 lbf·ft

2 FEMALE TORQUE HANDLES ADJUSTABLE - N·m ONLY

15112	Pro 50, 9 x 12mm, 10 - 50 N·m
15113	Pro 100, 9 x 12 mm, 20 - 100 N·m
15114	Pro 200, 9 x 12 mm, 40 - 200 N·m
15115	Pro 200, 14 x 18 mm, 40 - 200 N·m
15116	Pro 300, 14 x 18 mm, 60 - 300 N·m
15117	Pro 340, 14 x 18 mm, 60 - 340 N·m
15118	Pro 400, 14 x 18 mm, 80 - 400 N·m

2 FEMALE TORQUE HANDLES ADJUSTABLE - lbf·ft ONLY

15122	Pro 50, 9 x 12mm, 7.5 - 37.5 lbf·ft
15123	Pro 100, 9 x 12 mm, 15 - 75 lbf·ft
15124	Pro 200, 9 x 12 mm, 30 - 150 lbf·ft
15125	Pro 200, 14 x 18 mm, 30 - 150 lbf·ft
15126	Pro 300, 14 x 18 mm, 50 - 220 lbf·ft
15127	Pro 340, 14 x 18 mm, 50 - 250 lbf·ft
15128	Pro 400, 14 x 18 mm, 60 - 300 lbf·ft

2 FEMALE TORQUE HANDLES ADJUSTABLE - lbf·in ONLY

15132	Pro 50, 9 x 12 mm, 90 - 440 lbf·in
15133	Pro 100, 9 x 12 mm, 200 - 800 lbf·in
15134	Pro 200, 9 x 12 mm, 400 - 1800 lbf·in
15135	Pro 200, 14 x 18 mm, 400 - 1800 lbf·in
15136	Pro 300, 14 x 18 mm, 500 - 2500 lbf·in
15137	Pro 340, 14 x 18 mm, 500 - 3000 lbf·in
15138	Pro 400, 14 x 18 mm, 700 - 3500 lbf·in