










TESA TRI-O-BOR, Full Sets

Self-centring and self-aligning internal micrometers with 3-line contact with the part being inspected.

These micrometers measure through holes, blind bores and short centring shoulders.



-  DIN 863 T4 (Style 2) NFE 11-099
-  0,01 mm
-  Tungsten carbide tipped measuring bolts and cone
-  Inspection report with a declaration of conformity
-  0,002 mm
-  Supplied with 1 heat insulating sleeve No 00940020, 2 key No 00940001, 1 screwdriver No 00862801



| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |  |
| | | mm | Single micrometers | mm | Setting rings | mm | Extensions | mm |

COMPOSITION OF THE SETS:

| | | | | | | | | |
|----------|-----|----------|----------|-----------|----------|-----|----------|-----|
| 00910004 | BSC | 15 ÷ 30 | 00910005 | 15 ÷ 20 | 00840104 | 15 | 00940000 | 150 |
| | | | 00910006 | 20 ÷ 25 | 00840106 | 25 | | |
| | | | 00910007 | 25 ÷ 30 | | | | |
| 00910404 | BSD | 30 ÷ 60 | 00910405 | 30 ÷ 40 | 00840107 | 35 | 00940000 | 150 |
| | | | 00910406 | 40 ÷ 50 | 00840108 | 50 | | |
| | | | 00910407 | 50 ÷ 60 | | | | |
| 00910704 | BSF | 60 ÷ 90 | 00910705 | 60 ÷ 70 | 00840109 | 70 | 00940000 | 150 |
| | | | 00910706 | 70 ÷ 80 | 00840110 | 90 | | |
| | | | 00910707 | 80 ÷ 90 | | | | |
| 00911104 | BSG | 90 ÷ 120 | 00911105 | 90 ÷ 100 | 00840110 | 90 | 00940000 | 150 |
| | | | 00911106 | 100 ÷ 110 | 00840111 | 110 | | |
| | | | 00911107 | 110 ÷ 120 | | | | |

Extension for Depth Increase TESA TRI-O-BOR



| | |
|---|---|
|  |  |
| 00940000 | 150 |