



Caution! Modified settings on torque wrench (refer to note on page 189),
Chrome Alloy Steel, chrome plated.



Code	 mm	 "	L mm	b mm	a mm	S mm	 g	
01 20 00 08	8	1/4	25.5	19.8	6.3	14.6	19	1
01 20 00 09	9	1/4	25.5	19.8	6.3	14.6	21	1
01 20 00 10	10	1/4	25.5	19.8	6.3	14.6	20	1
02 20 00 11	11	3/8	32	22.2	6.3	17.4	36	1
02 20 00 12	12	3/8	34.3	25.4	6.3	18.2	37	1
02 20 00 13	13	3/8	34.3	25.4	6.3	17.8	36	1
02 20 00 14	14	3/8	37.7	30	6.3	20.8	46	1
02 20 00 15	15	3/8	37.7	30	6.3	20.4	45	1
02 20 00 16	16	3/8	37.7	30	6.3	19.9	45	1
02 20 00 17	17	3/8	42.5	38	6.3	23.8	62	1
02 20 00 18	18	3/8	42.5	38	6.3	22.9	61	1
02 20 00 19	19	3/8	42.5	38	6.3	22.4	64	1
02 20 00 20	20	3/8	42.4	38	6.3	25	55	1
02 20 00 21	21	3/8	44.5	41	6.3	23.6	59	1
02 20 00 22	22	3/8	44.5	41	6.3	24.2	64	1
02 20 00 23	23	3/8	44.5	41	6.3	25.8	64	1
02 20 00 24	24	3/8	44.4	41	6.3	26.2	60	1
02 20 00 25	25	3/8	47	45	8	26.4	75	1
02 20 00 26	26	3/8	47	45	8	27.6	80	1
02 20 00 27	27	3/8	47	45	8	27.6	76	1
02 20 00 28	28	3/8	50	50	8	29.3	78	1
02 20 00 30	30	3/8	50	50	8	29.3	84	1
02 20 00 32	32	3/8	53	57	8	30.5	95	1
02 20 00 34	34	3/8	54.5	60	8	31.6	107	1
02 20 00 36	36	3/8	56.5	62	8	32.8	100	1
02 20 00 40	40	3/8	63	70	8	37.6	130	1
02 20 00 41	41	3/8	63	70	8	37.2	130	1
02 20 00 42	42	3/8	63	70	8	37.7	125	1
02 20 00 46	46	3/8	72	82	8	43.1	191	1
02 20 00 50	50	3/8	75	88	8	45.4	217	1