

540a HD**CROW-FOOT spanners Heavy Duty**

For particularly high loadings, e.g. stainless steel screw fittings.

Full use of jaws in conjunction with standard ratchets.

Caution! Modified settings on torque wrench (refer to note on page 189), chrome plated. Supplied without ratchet.

5



Code			L mm	b mm	a mm	S mm	 g	
02 50 10 34	9/16	3/8	43.4	32	11	26.8	52	1
02 50 10 36	5/8	3/8	45	34.8	11	27.7	58	1
02 50 10 38	11/16	3/8	47.2	38	11	28.6	69	1
02 50 10 42	13/16	3/8	51	46.4	11	30.5	113	1
02 50 10 44	7/8	3/8	52	48	11	31.3	99	1
02 50 10 46	15/16	3/8	54	51.2	11	32.3	129	1
02 50 10 48	1	3/8	56	53.4	11	33.2	133	1
02 50 10 50	1 1/16	3/8	57	53.8	11	34.1	124	1
02 50 10 52	1 1/8	3/8	59	53.8	11	35	128	1
02 50 10 56	1 1/4	3/8	62	60	11	36.8	153	1
02 50 10 62	1 7/16	3/8	66.5	66	11	39.6	172	1
03 50 10 64	1 1/2	1/2	76	70	16	45	310	1
03 50 10 69	1 13/16	1/2	85	84	16	49.6	400	1
03 50 10 72	2	1/2	89	90	16	52.3	451	1
03 50 10 74	2 1/8	1/2	91.5	92.8	16	54.2	460	1
03 50 10 75	2 3/16	1/2	93	96	16	55.1	480	1
03 50 10 76	2 1/4	1/2	95	99	16	56	500	1