

PROFESSIONAL TORQUE WRENCHES
MODELS 650 - 1500 ADJUSTABLE



For precision applications to 1500 N·m

- Exceptionally clear torque signal from unique mechanism
- Non length dependant so can be used with or without the supplied extension handle (optional on Model 650)
- Extension handle significantly reduces operator effort to achieve high torque values
- Accurate to ±3% of reading
- Supplied with traceable calibration certificate

2 ADJUSTABLE RATCHET - DUAL SCALE

14037	Pro 650, 3/4", 130 - 650 N·m, 100 - 480 lbf·ft
14015	Pro 800, 3/4", 200 - 800 N·m, 150 - 600 lbf·ft
14016	Pro 800, 1", 200 - 800 N·m, 150 - 600 lbf·ft
14002	Pro 1000, 3/4", 300 - 1000 N·m, 220 - 750 lbf·ft
14003	Pro 1000, 1", 300 - 1000 N·m, 220 - 750 lbf·ft
14004	Pro 1500, 3/4", 500 - 1500 N·m, 370 - 1100 lbf·ft
14005	Pro 1500, 1", 500 - 1500 N·m, 370 - 1100 lbf·ft

2 ADJUSTABLE RATCHET - N·m ONLY

14038	Pro 650, 3/4", 130 - 650 N·m
14024	Pro 800, 3/4", 200 - 800 N·m
14025	Pro 800, 1", 200 - 800 N·m
14026	Pro 1000, 3/4", 300 - 1000 N·m
14027	Pro 1000, 1", 300 - 1000 N·m
14028	Pro 1500, 3/4", 500 - 1500 N·m
14029	Pro 1500, 1", 500 - 1500 N·m

2 ADJUSTABLE RATCHET - lbf·ft ONLY

14044	Pro 650, 3/4", 100 - 480 lbf·ft
14045	Pro 800, 3/4", 150 - 600 lbf·ft
14046	Pro 800, 1", 150 - 600 lbf·ft
14047	Pro 1000, 3/4", 220 - 750 lbf·ft
14048	Pro 1000, 1", 220 - 750 lbf·ft
14049	Pro 1500, 3/4", 370 - 1100 lbf·ft
14050	Pro 1500, 1", 370 - 1100 lbf·ft



2 TORQUE HANDLE ADJUSTABLE - DUAL SCALE

14040	Pro 650, 22mm spigot, 130 - 650 N·m, 100 - 480 lbf·ft
-------	---



2 FEMALE TORQUE HANDLES ADJUSTABLE - DUAL SCALE

14041	Pro 650, 14 x 18mm, 130 - 650 N·m, 100 - 480 lbf·ft
-------	---

PROFESSIONAL TORQUE WRENCHES
MODELS 650 - 1500 'P' TYPE



2 RATCHET PRODUCTION 'P' TYPE
(Must be set using a Torque Tester, see pages 48-51)

14039	Pro 650, 3/4", 130 - 650 N·m, 100 - 480 lbf·ft
14017	Pro 800, 3/4", 200 - 800 N·m, 150 - 600 lbf·ft
14018	Pro 800, 1", 200 - 800 N·m, 150 - 600 lbf·ft
14007	Pro 1000, 3/4", 300 - 1000 N·m, 220 - 750 lbf·ft
14008	Pro 1000, 1", 300 - 1000 N·m, 220 - 750 lbf·ft
14009	Pro 1500, 3/4", 500 - 1500 N·m, 370 - 1100 lbf·ft
14010	Pro 1500, 1", 500 - 1500 N·m, 370 - 1100 lbf·ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)



8 MODELS 650-1500 ACCESSORY

14142	Extension Handle (included with 800-1500 Models as standard)
-------	--



2 TORQUE HANDLES PRODUCTION 'P' TYPE
(Must be set using a Torque Tester, see pages 48-51)

14042	Pro 650, 22mm spigot, 130 - 650 N·m, 100 - 480 lbf·ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)



2 FEMALE TORQUE HANDLES PRODUCTION 'P' TYPE
(Must be set using a Torque Tester, see pages 48-51)

14043	Pro 650, 14 x 18mm, 130 - 650 N·m, 100 - 480 lbf·ft
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)



All models supplied in carry case